



Wireless Solutions for Fire & Security

## Remote Indicator Unit

- Remote Fire Indication
- Easy Installation



## Overview

The Remote Indicator Unit provides remote fire indication up to 3 metre away from the Radio Detector. The Detector and Remote Indicator Units are both supplied with connected two way terminal blocks for simple connection. Optical Smoke, Multisensor, Heat Class CS And Heat Class A1R detection variants are available.

### Ordering Information

The Remote Indicator Unit is supplied with the following products:

**FCX-100-101** - FireCell Optical Smoke Detector c/w Remote Indicator Unit

**FCX-120-101** - FireCell Heat Detector (Class A1R) c/w Remote Indicator Unit

**FCX-120-111** - FireCell Heat Detector (Class CS) c/w Remote Indicator Unit

**FCX-130-101** - FireCell Multisensor Smoke Detector c/w Remote Indicator Unit



## Specification

Dimensions:	85(H) x 85(W) x 45(D)mm
Operating Temperature:	N/A
Humidity:	N/A
Supply:	N/A
IP Rating:	N/A
Operating Frequencies:	N/A
Output Transmitter Power:	N/A
Standards:	N/A
Cabling Requirements:	Minimum spec; Multi Core 7/0.18mm (0.22mm <sup>2</sup> ) Alarm Cable compliant to BS4737 (Maximum 3m length of cable)



EMS Group Head Office  
Technology House  
Sea Street  
Herne Bay  
Kent CT6 8JZ  
England  
Tel: +44 (0) 1227 369570  
Fax: +44 (0) 1227 369679  
Email: [enquiries@msgroup.co.uk](mailto:enquiries@msgroup.co.uk)

[www.msgroup.co.uk](http://www.msgroup.co.uk)

An ISO9001:2008 approved company



Dealer Information:

The information contained within this literature is correct at time of publishing. The EMS Group reserves the right to change any information regarding products as part of its continual development enhancing new technology and reliability. The EMS Group advises that any product literature issue numbers are checked with its head office prior to any formal specifications being written.

Part No: RIM, v2.0